

CK3010/3310

KIOTI COMPACT TRACTOR




KIOTI
run ahead of the pack

Specifications



MODEL		CK3010		CK3310	
		MANUAL		HST	
ENGINE					
Model		3A139LWB			
Engine Max HP @ 2900rpm		hp	30	33	
Engine Gross		hp	28	30	
Rated revolution		cc	2600		
Total displace		rpm	1393		
Fuel tank capacity		ℓ	25		
DRIVE TRAIN					
Clutch		Dry single			
Transmission		Manual		Hydrostatic	
Speeds		3 x 2 (6F2R)		INF. 2	
Differential lock (rear)		Standard			
Brake		Wet disc type			
PTO		Transmission		Live	
	Rear	rpm	540		
	Mid(Optional)	rpm	2,000		
HYDRAULIC SYSTEM					
Pump		Gear(Tandem)			
Total Pump capacity at maximum flow		ℓ /min	42.9		
3-point hitch		Cat. 1			
Maximum lifting capacity(24 behind lift point)		kg	739(546)		
Hydraulic lift control system		Position control			
Steering		Hydrostatic Power Steering			
No. of standard remote valve (Rear)		1 (Opt)		1 (Std)	
TIRE SIZE					
AG Tire	Front	7-12			
	Rear	11.2-16			
TRAVELING SPEEDS					
Forward		km/h	1.20-17.34		0-17.15
Reverse		km/h	1.48-6.73		0-12.01
DIMENTIONS					
Overall length(including 3-pt hitch)		mm	2,790		
Overall width(minimum tread)		mm	1,250		
Overall height(from top of ROPS)		mm	2108		
Wheelbase		mm	1,520		
Min. ground clearance		mm	330		
Tread	Front	mm	989		
	Rear	mm	950		
Weight with ROPS		kg	1,025		

Standard Equipment

- Joystick lever with mid mount valve for front loader
- Cruise Control (HST model)
- Hydraulic Power Steering

Optional Equipment

- Front Weight
- Working lamp
- 7-Pin Connector
- Rear Remote Hydraulic Valve (Manual Model Only)



Power Farming Wholesale
 86 Thames Street, PO Box 6, Morrinsville
 3300 New Zealand
Tel 07 902 2200 **Fax** 07 902 2201
www.kiotitractors.co.nz

Dealer Imprint Area